

HIGH SENSITIVITY PRESSURE SUSTAINING PILOT VALVE

Model #83

This pilot integrates all principal functions of a 2-Way control circuit in a single assembly.

It is a high sensitivity, direct acting valve, actuated by a pressure responsive diaphragm, which tends to reach equilibrium with the set spring force.

The pilot modulates open as upstream pressure rises above set point. An integral needle valve acts as an upstream flow restrictor as well as a closing speed control.

Typical Applications

- Modulating Altitude Level Control Valves (at reservoir outlet)
- High Sensitivity Pressure Sustaining Valves

Technical Data

Pressure Rating: 16 bar; 230 psi

Working Temperature: Water up to 60°C; 150°F

Flow Factor: Kv 1.1; Cv 1.3

Valve Size Range: Small - Medium

Standard Materials:

Body & Cover: Brass

Diaphragm Covers: Fusion bonded epoxy coated Steel

Elastomers: NBR

Internals: Stainless Steel & Brass

Spring: Galvanized Steel

Optional Materials:

Metal Parts: Stainless Steel, Nickel Aluminum Bronze, Hastalloy

Elastomers: EPDM, FPM (Viton®)

Adjustment Range

Code	Pressure		
	Meter	Feet	
M1	2-8	7-26	Standard
M6	2-14	7-46	
M5	5-22	17-72	Optional
M4	15-35	49-115	
M8	25-70	82-230	


Connections

Z - Upstream **A** - Valve control chamber **C** - Downstream

Sensing - For altitude control – still point at reservoir bottom

For pressure sustaining – to valve upstream

* Always recommended to refer to control diagram



Weights: M1/M6 -10 Kg; 22 lbs. M5 -11 Kg; 24 lbs.
M4 -19 Kg; 42 lbs. M8 -22 Kg; 49 lbs.

All images in this catalog are for illustration only



www.bermad.com

The information contained herein may be changed by BERMAD without notice. BERMAD shall not be held liable for any errors.
© Copyright 2009-2019 BERMAD CS Ltd. August 2019