



BERMAD WATER TECHNOLOGIES

ABN: 62 093 801 220

26 Brand Drive, PO Box 506
Thomastown VIC 3074, Australia

Telephone: +61(3) 9464-2374

Facsimile: +61(3) 9464-2382



Document no : D-251024-3-CK
Date : 25th Oct 2024
Revision no : Rev 0

Questionnaire for Air Release Valve in Sewage Rising Main

In order to correctly select the optimum air release valve for your application we require to best understand your installation requirements. If this questionnaire can be returned to BWT, we can ensure the correct product is supplied fit for purpose. Note : We have requested a high degree of information that may not all be available. Simply supply what you can and we can discuss a product most suitable.

1. Liquid: Raw Effluent Raw effluent after pump macerator.....
2. Primary Treated Effluent Secondary Treated effluent for Irrigation
3. Pipe diameter :mm New Pipe..... Old existing pipe.....
4. Pipe material PVC..... Poly..... GRP..... DICL St/Steel.....
5. Pressure class of pipe : PN6..... PN9..... PN12.... PN16..... PN25.....
6. Pressure in pipe at air valvesKpa minimumKpa maximum
7. QA valves approved to AS4883..... Appraised to WSAA.....
8. Flow rate of the pump or gravity system l/s
9. Application Pump station discharge prior to check valve.....
Pump station Discharge after pump non return valve.....
Along transfer pipeline at high spot..... Prior to a pipe section valve.....
10. If you can provide a pipeline profile, we can look at the application closer.....
11. Additional comments :
.....

Submitted by : Date/...../.....

Project name : (optional)